



# MALLAZUL<sup>®</sup> PROTECT<sup>MR</sup>





# MALLAZUL<sup>®</sup> © PROTECT<sup>MR</sup>



REFORZADA CON ALAMBRES GALVANIZADOS FORRADOS CON PVC.

| ABERTURA (mm) |    |    |    |    |
|---------------|----|----|----|----|
| 13            | 20 | 25 | 38 | 50 |

| MEDIDAS (pulg) |      |    |        |    |
|----------------|------|----|--------|----|
| 1/2"           | 3/4" | 1" | 1 1/2" | 2" |

| DIÁMETRO ALAMBRE PVC AZUL (mm) |      |      |      |      |
|--------------------------------|------|------|------|------|
| 0.85                           | 0.85 | 1.00 | 1.00 | 1.00 |

| CALIBRE ASWG |        |        |        |        |
|--------------|--------|--------|--------|--------|
| CAL 23       | CAL 23 | CAL 22 | CAL 20 | CAL 20 |

| ALTURA (m) |      |      |      |      |
|------------|------|------|------|------|
| 0.90       | 0.90 | 0.60 | 1.50 | 1.50 |
| 1.20       | 1.20 | 1.00 | 1.75 | 1.60 |
|            |      | 1.20 |      | 1.75 |
|            |      | 1.50 |      |      |
|            |      | 1.75 |      |      |
|            |      | 2.00 |      |      |

| LONGITUD (m) |    |    |    |    |
|--------------|----|----|----|----|
| 15           | 15 | 15 | 15 | 15 |
| 45           | 45 | 45 | 45 | 45 |

NORMAS DE FABRICACIÓN ASTM A-641-98 | ASTM A-390-95



[www.puntoazulmx.com](http://www.puntoazulmx.com)



271 718 0700